

FOCUS V

IDEAL FOR BULK

The FOCUS V freezer has an elegant, yet robust, design to optimally catch the attention of your customers. The lid design, the improved insulation and the heated frame ensure minimum ice build-up.

Cyclopentane is used as blowing agent and the cabinets are CFC free.



FOCUS 106 V WITH BULK CONTAINER




FOCUS 106 V WITH OPEN LID

	FOCUS 73 V	FOCUS 106 V	FOCUS 131 V
Climate class 4	4	4	4
Ambient temperature range	+16 to +30	+16 to +30	+16 to +30
Climate class 7	7	7	7
Ambient temperature range	+16 to +35	+16 to +35	+16 to +35
Gross volume, litres	161	270	352
Net volume, litres	113	193	254
Temperature range inside unit	-16 to -23	-16 to -23	-16 to -23
Standard refrigerant	R600a	R600a	R600a
Energy consumption / 24 h kwh at 30 deg. C	1,8	2,53	2,83
Annual energy consumption kwh	664	926	1033
Energy efficiency index	54,9%	67,9%	66,1%
Energy class	D	E	E
Input power (watt)	141	153	203
DIMENSIONS			
External dimensions (WxDxH)	726*656*878	1056*656*878	1306*656*878
Internal dimensions (WxDxH)	570*500*670	900*500*670	1150*500*670
Dimension A	726	1056	1306
Dimension B	656	656	656
Dimension C	890	890	890
Dimension D	570	900	1150
Dimension E	370	700	950
Dimension F	500	500	500
Dimension G	725	725	725
Dimension H	475	475	475
Dimension I	770	770	770
Insulation (mm)	75	75	75
ACCESSORIES			
Dividers	Optional	Optional	Optional
Container for bulk food, PLASTD21	Optional (2 pcs)	Optional (3 pcs)	Optional (4 pcs)
Max. number of baskets (model C75-01/ C75-02)	2/3	4/4	5/6
Castors	Incl.	Incl.	Incl.
Castors w. brakes	Optional	Optional	Optional
Lock	Optional	Optional	Optional
Thermometer	Optional	Optional	Optional
Internal light	Optional	Optional	Optional
OTHER DATA			
Outer cabinet	White	White	White
Inner cabinet	Aluminium	Aluminium	Aluminium
Inner cabinet: option	Steel inner liner	Steel inner liner	Steel inner liner
Graphics	Optional	Optional	Optional
Type of cooling	Static	Static	Static
Type of defrost	Manual	Manual	Manual
Power	220V/50Hz	220V/50Hz	220V/50Hz
Power 110volt / 60 hz	Optional	Optional	Optional
UL approval / DOE approval	Yes	Yes	Yes
Thermostat	Mechanical	Mechanical	Mechanical
Net weight, kg	44	54	62
Gross weight, kg	47	58	66
SHIPPING			
20' cont. Capacity	42	30	24
40' cont. Capacity	90	64	50
40' HC cont. Capacity	126	88	62
Standard Trailer capacity	153	108	90



FOOD BUCKET
(FDA-APPROVED FOR FOOD)



DRAIN

FEATURES

- HC refrigerants as standard
- Environmentally friendly
- Low service costs
- Perfect view to the products
- Long life
- Available in all climate classes
- Minimum icebuild-up
- Designed for transport
- Eye Catching design
- 75 mm insulation
- Also available as combination of cooler and freezer- see page 53.
- Accessories including baskets - see page 64
- Graphics (option)
- LED internal light (option)